



















Warranty		10 years*	 Environment, health and safety
Composition		83% vinyl 7% fiberglass 10% PET	Recycled Content Yes
Backing		Vinyl + Felt	Acoustical layer 70% recycled content
 Total thickness	ISO 1765	5 mm 0.20"	Reach Compliant
 Total weight	ISO 8543	3000 g/m ² 88.5 oz/yd ²	LEED v4 Compliant (LEED Contributing Product)
 Roll width	EN ISO 24341	ca. 200 cm ca. 6'7"	BREEAM International Compliant
 Roll length	EN ISO 24341	ca. 30 m 32.8 yd	CDPH Standard Method V1.2 Pass
 Tile size 16 pcs per box	EN 994	50 cm x 50 cm 19.69" x 19.69"	BREEAM[®] NOR Pass
 Level of Use	EN 1307 ASTM D5252	Class 33 Heavy commercial use	French VOC Regulation A+ Certified
Foot traffic test	ASTM D6119-12	Heavy traffic	French CMR components Pass
 Castor chair suitability	EN 985	Continuous use	AGBB/ABG Pass
 Reaction to fire	EN 13501-1 ASTM E84	Bfl-s1 Class I - A rating	Belgian VOC Regulation Pass
Critical radiant flux	ASTM E648-15e1 NFPA	0,84 W/cm ² Class I	Indoor Air Comfort Gold Pass
Smoke density	ASTM E622	< 300	Blue Angel (RAL UZ120) Pass
 Walking test	ISO 6356 AATCC 134-2006	< 2 kv Permanently antistatic	SundaHus B rating
 Light fastness	ISO 105-B02	≥ 8	EN 717-1 E1
 Slip resistance	EN 13893 ASTM C1028-07 DIN 51130 EN 13036-4	≥ 0,3 0,85 R9 65	M1 Protocol of July 2017 Pass
 Impact sound reduction	ISO 10140	19 dB	Plasticizer Content Phthalate Free
 Acoustical absorption	ISO 354	aw = 0,15	 
 Walking noise reduction	EPLF 021029-3	SL70	
 Dimensional stability	EN 986 ISO 2551	Meets the requirements	  
 Thermal resistance	ISO 8302	Suitable for underfloor heating	
 CE Certificate	EN 14041	0493-CPR-0151	 

*Terms and conditions are available on request